

AD-808 UHF 4-Channel Active Antenna Combiner

Key Features



- Wideband frequency ranges from 470~960 MHz.
- Operates with up to 4 transmitters.
- Input signal indicator (threshold above +6 dBm).
- Maximum RF input power +20 dBm (100 mW).
- Ideal intermodulation characteristics (3rd order IM< -57 dBc under full band performance +15 dBm two-tone test)

Accessories

MI-808T	Stereo Transmitter
FB-71	Rack Mount Kit

Technical Specifications

Frequency Range	470~960MHz
Full System Gain	0 ± 2dB
VSWR Input / Output	< 1.5: 1
Maximum RF Input Power	+20dBm
Input Signal Indicator Threshold	+6dBm
Power Consumption	9.12W (12V, 760mA)
Input / Output Connectors	TNC female (4-input, 1-output)
Dimensions	210(W)x44(H)x206(D)mm / 8.3(W)x1.7(H)x8.1(D)"
Weight	1.1kg / 2.4lbs



MIPRO Electronics Co., Ltd

Headquarters: 814 Pei-kang Road, Chiayi, 60096, Taiwan
 Tel: +886.5.238.0809 | Fax: +886.5.238.0803
 www.mipro.com.tw | mipro@mipro.com.tw